



DF Bond-Aid



DF Bond-Aid is specifically designed to provide strong bonding properties on the solid surface structures and interior surface of gypsum or other plaster-based wall coating. Bond-Aid has a combination of ingredients that helps to form a strong surface and also enhance the bonding capabilities. You do not need any special treatment to be done before the application of Bond-Aid. Bond-Aid produces a layer for the treatment of surfaces that acts as a high-performance bonding agent for gypsum or sand cement plaster after the application on smooth surface. Bond-Aid is used to add tensile bond strength to smooth surfaces while carrying out Gypsum Plastering. This is done by suspending the Co-Polymers in a unique Chemical solution to ensure both Chemical and Mechanical Bonding.

Technical Specification

Film Characteristics	Green granular flexible
Appearance	Green
Tensile Bond Strength	>2 MPA
Coverage	Approx. 50 sqft / Kg
Chemical Composition	Polymer based liquid



Product Features



SINGLE COAT
APPLICATION



COARSE & LIQUID
PARTICLE BONDING



24 HOURS
DRYING TIME



SUITABLE FOR GYPSUM &
SAND CEMENT PLASTER



LARGE
COVERAGE AREA

Packaging & Branding

DF Bond-Aid is stored in a plastic bucket. On the bucket it is printed with the name of the product along with the features, methods of application, expiry date for the product, address, and the safety parameters.

Sizes

It is available in 20 Kg, 10 Kg, 5 Kg, and 1 Kg buckets.

APPLICATION METHOD

FOLLOW 3 EASY STEPS
FOR APPLICATION



1

OPEN AND STIR THE
CHEMICAL PROPERLY



2

APPLY WITH A PAINT
BRUSH OR ROLLER



3

DRY FOR 24 HOURS.
SURFACE READY FOR
PLASTERING

Caution

- Wash Gently with water after use of material
- Keep away from eye contact, incase of eye contact wash throughly with water.
- In case of emergency kindly seek advise from Doctors.